

Fiber OWL 7X Optical Power Meter

Part #: F7X

Features

- Optical power measurement
- Auto-wavelength recognition and data storage reduces testing time and human error
- Integrated length testing port for accurate end-to-end link length measurements, a critical factor for standards-based link budget calculation
- Re-chargeable Lithium Polymer battery
- Up to 50 hours continuous operation
- Includes auto-shutdown feature to conserve battery life
- High accuracy
- NIST Traceable

When used with OWL fiber optic light sources (sold separately):

- Optical loss measurement
- Automatic wavelength switching (when used with WaveSource Pro light sources) allows for automatic dual-wavelength optical referencing and power/loss testing
- Standards-based link certification for optical fiber links
- Unlimited job configurations
- User-friendly Link Wizard with helpful color on-screen diagrams to help guide the setup process
- Color LCD indicates PASS / FAIL status based on color
- Up to 10,000 test readings can be stored in memory
- Prints official certification reports via OWLView certification software

Upgrade options:

- Visual Fault Locator port for near-end fault location and visual fiber identification (model #: **F7V**)



Factory located in the
Heartland of America



Certifying Optical Power Meter w/integrated length testing

Applications

The Fiber OWL 7X (model #: **F7X**) is a high accuracy, high resolution, microprocessor controlled optical power meter. The detector port has a 75dB dynamic range making it ideal for a wide array of fiber optic testing applications, including standards-based fiber link certification (when used with separate light sources; sold separately).

The unit is housed in an attractive handheld case made from high impact plastic surrounded by a protective rubber boot, includes a high-resolution color LCD display, and an intuitive keypad for convenient data entry. The universal detector port includes two adapter caps: one for 2.5mm ferrule connectors, such as SC, ST, and FC; and one for 1.25mm ferrule connectors such as LC and MDC. The unit will operate up to 50 hours on its high-capacity Lithium Polymer battery, and has built-in auto shutdown.

The power meter port is equipped with an auto-wavelength recognition feature called AUTO MODE that automatically switches the wavelength being received from compatible OWL dual-wavelength, auto-testing light sources, such as OWL WaveSource Pro series light sources (sold separately). The detector senses the auto-switching signal from the WaveSource Pro light source, then automatically switches to that wavelength accordingly. This feature allows for simultaneous dual-wavelength optical referencing and power/loss testing, which increases productivity by decreasing testing time and human error.

When used with OWL fiber optic light sources (sold separately):

the power meter includes a built-in loss wizard that helps you easily calculate the allowable loss for the fiber runs that you will be measuring. The meter stores physical fiber information for an unlimited number of jobs/projects, including link name, date, fiber type, fiber length, connectors, splices, temperature, and calculated or user-defined reference power values. In addition, the meter will store thousands of measured data points with customizable run name information.

The stored information can be selectively viewed, edited (measured again), printed, or deleted. Data may be downloaded via the built-in USB download port to our free OWLView software to produce professional certification reports.



Optical Wavelength Laboratories

MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT



Optical Wavelength Laboratories (OWL)
N9623 Old Hwy 12 • Whitewater, WI 53190
Phone (262) 473-0643 • Fax: (262) 473-8737
Internet: OWL-inc.com

Fiber OWL 7X Optical Power Meter

Part #: F7X

Certifying Optical Power Meter w/integrated length testing

FIBER OWL 7 OPTICAL POWER METER (P/N: F7X)

Key Specifications	
Detector Type	InGaAs
Calibrated Wavelengths ¹	850, 980, 1300, 1310, 1490, 1550, 1625
Measurement Range	+5 to -70 dBm
Accuracy	±0.15 dB
Display Resolution	0.01 dB
Battery Life	Up to 50 hours (Lithium Polymer)
Detector Connector Type	2.5mm/1.25mm universal
Data Storage	Up to 10000 data points
Displayed Measurement Units	dBm, dB, mW, μW, nW
Modes of Operation	CERT, LOSS, OPM
Length Test Range / Accuracy	up to 25 km / ±2.5 m
Length Tester Connector Type	SC
Display Type	Hi-resolution Color LCD
Auto-shutdown	Yes
Operating Temperature	-10 to 55° C
Storage Temperature	-30 to 70° C
Dimensions	2.9 x 4.49 x 1.3 in. (72.9 x 112.3 x 31.8 mm)
Weight	12 oz. (373g)

1: Bold wavelengths are NIST Traceable

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

Power Meter Ports

LENGTH TEST PORT

works with both multimode and singlemode fibers



UNIVERSAL DETECTOR PORT

Includes:
2.5mm adapter (SC,ST, FC)
1.25mm adapter (LC)

Supported Cabling Standards

TIA	568-C.3	568-3.D		
ISO	11801	14763-3		
Ethernet	1G	10G	40G	100G
FTTH	Class A	Class B	Class C	
USER DEFINED	Fixed budget	Calculated budget		

Power Meter Upgrade Options

Option	Model #:
Integrated Visual Fault Locator	F7V

Light Source Options

Model #:	Description	MM: 850	MM:1300	SM: 1310	SM: 1550	VFL
WPMS	WaveSource Pro Quad	AUTO-SWITCHING		AUTO-SWITCHING		—
WPMX	WaveSource Pro MM	AUTO-SWITCHING		—	—	—
WPMV	WaveSource Pro MM/VFL	AUTO-SWITCHING		—	—	✓
WPSX	WaveSource Pro SM	—	—	AUTO-SWITCHING		—
WPSV	WaveSource Pro SM/VFL	—	—	AUTO-SWITCHING		✓

Replacement Accessories

Description	Part #:
2.5mm Universal Adapter Cap (SC, ST, FC)	U2.5-4
1.25mm Universal Adapter Cap (LC, MU, MDC)	U1.25-4
USB Download Cable	USB-1
USB Charging Block	WS-USB

Cleaning Accessories

Description	Part #:
Patch Cable Ferrule Connector Cleaner	FCC-2
Replacement Tape Reel for FCC-2	FCC-2R
2.5mm In-Adapter Ferrule Connector Cleaner	OC-2
1.25mm In-Adapter Ferrule Connector Cleaner	OC-1

Fiber Optic Inspection Microscopes

Description	Part #:
Direct-view Field Microscope	FS400
USB Fiber Optic Videoscope	VS-400-U



Optical Wavelength Laboratories

MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT



Optical Wavelength Laboratories (OWL)
N9623 Old Hwy 12 • Whitewater, WI 53190
Phone (262) 473-0643 • Fax: (262) 473-8737
Internet: OWL-inc.com