

Fiber OWL 4 BOLT MM Test Kit

SKU: KIT-FO4B-WSMDxx (see connector options below)

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **Fiber OWL 4 BOLT MM Test Kit** contains the tools necessary for certifying fiber optic links against a myriad of popular cabling standards in singlemode and multimode networks.

The **Fiber OWL 4 BOLT optical power meter** is multimode and singlemode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation (including integrated fiber link length testing), and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 1000 fiber runs may be stored, then downloaded to a PC for report generation using our OWL Reporter software.

It also includes intelligent automated testing functions, such as automatic dual-wavelength storage and auto-wavelength recognition, which reduce testing time and human error.

The **WaveSource MM fiber optic light source** is designed for accurate testing and certification of multimode (850nm & 1300nm) networks. Its dual-wavelength outputs are temperature-stabilized for accurate measurements.

The **WaveSource MM** has a built-in auto-wavelength switching protocol designed to synchronize the wavelength of the **Fiber OWL 4 BOLT** with the current output wavelength.

Three connector options are available (ST, SC, and FC), and is upgradeable to include 1310 & 1550nm singlemode sources.

Kit Contents

| | | | | |
|---------------------|-----------------------|-------------------------|-----------------|------------------|
| Power Meter: | Fiber OWL 4 BOLT | Light Source: | WaveSource MM | |
| Accessories: | OWL Reporter software | Product manuals | Download cable | 9-volt batteries |
| NIST certificate | Carrying case | Protective rubber boots | Carrying straps | |



Connector styles or placement may vary from photo

Multimode Fiber Certification Test Kit with integrated fiber length testing

Features

- Certification of multimode fiber links at 850nm and 1300nm
- Auto-wavelength recognition and automatic data storage reduce testing time and human error
- Integrated fiber optic length tester for accurate link length measurements
- Data storage for up to 1000 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects
- Built-in loss wizard for calculation of maximum allowable loss values (link budget)
- USB interface for continuous data logging, report printing, or data downloading
- OWL Reporter software for printing formatted fiber certification reports
- Absolute or relative mode for giving you instant pass/fail results
- Selectively view, delete or resample data points

Supported Cabling Standards:

| | | |
|---------------|---------------|---------------------|
| EIA/TIA 568-B | ISO/IEC 11801 | 10-Gigabit Ethernet |
| 1000Base-SX | 1000Base-LX | 100Base-FX |
| 10Base-FB | 10Base-FL | FDDI |
| ATM-155 | ATM-622 | Fibre Channel |
| Token Ring | | |

Also supports 2 user-definable standards



ASSEMBLED IN USA

N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



Fiber OWL 4 BOLT MM Test Kit

SKU: KIT-FO4B-WSMDxx (see connector options below)

Multimode Fiber Certification Test Kit
with integrated fiber length testing

Specifications

Fiber OWL 4 BOLT Optical Power Meter

| | |
|---|-----------------------------|
| Detector Type | InGaAs |
| NIST Traceable Wavelengths | 850nm, 1300, 1310nm, 1550nm |
| Additional Wavelengths | 980, 1490, 1625nm |
| Optical Power Measurement Range | +5 to -70 dBm |
| Accuracy | ±0.15 dB |
| Resolution | 0.01 dB |
| Battery Life | up to 100 hours (9V) |
| Connector Type | Universal |
| Data Storage Points | up to 1000 |
| Download Data Points | OWL Reporter Software |
| Power Units Displayed | dBm, dB, μW |
| Modes of Operation | Simple / Certification |
| Optical Fiber Length Measurement Range | up to 25 km |
| Optical Fiber Length Measurement Accuracy | ±2.5 meters |
| Battery Capacity Display | Yes |
| Backlight | Yes |
| NIST Traceable | Yes |
| Auto-shutdown | Yes |
| Serial Port Diagnostic | Yes |
| Operating Temperature | -10 to 55 C |
| Storage Temperature | -30 to 70 C |
| Width | 3.48" |
| Height | 6.48" |
| Depth | 1.1" |
| Weight | 373g (12 oz.) |

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.


WaveSource MM Fiber Optic Light Source

| | |
|-------------------------------|------------------------------|
| Launch Method (multimode) | LED |
| Connector | ST, SC, or FC |
| Center Wavelength (850nm) | 850 +30/-10nm |
| Center Wavelength (1300nm) | 1300 ±50 nm |
| Spectral Width (FWHM; 850 nm) | 50nm |
| Spectral Width (FWHM; 1300nm) | 180nm |
| Output Power | -20.0 dBm |
| Initial Accuracy | 0.1 dB |
| Output Modes | Continuous Wave Modulated |
| Battery Life | up to 30 hrs. |
| Battery Type | 9V alkaline |
| Battery Capacity Display | Yes |
| Operating Temperature | 0 to 55° C |
| Storage Temperature | 0 to 75° C |
| Width | 2.75" |
| Height | 4.94" |
| Depth | 1.28" |
| Weight | 154g |

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>