

Micro OWL 2/WaveSource SM/VFL Test Kit

SKU: KIT-M2-WSVSDst
SKU: KIT-M2-WSVSDsc

Singlemode Fiber Test Kit

Overview

Many fiber optic network bids and Requests For Quote (RFQ) are citing cabling standards to specify the set of guidelines (such as fiber length) that the network installer must follow during the network installation. Adherence to such standards is meant to ensure the quality of the installation and guarantee that the network will perform as it was designed.

The process of testing a network installation to ensure its adherence to specified standards is called certification, and often requires hard-copy documentation as proof of adherence to standards.

The **Micro OWL 2 / WaveSource SM / VFL Test Kit** contains the tools necessary for certifying singlemode fiber optic links against a myriad of popular cabling standards, including two user-customizable standards.

The **Micro OWL 2 optical power meter** is multimode and singlemode ready, and contains a user-friendly Fiber Link Wizard that performs link budget calculation, and sets a reference value using the characteristics of the link. This reference is the PASS/FAIL threshold and is calculated against the chosen standard. Up to 1000 fiber runs may be stored, and serially downloaded to a PC for report generation using our OWL Reporter software. Its universal port allows connections to ST, SC, and FC, and also includes a 1.25mm universal port for connection to LC, MU, and other SFF connectors.

The **WaveSource SM/VFL** singlemode light source has dual wavelength outputs (1310 nm & 1550 nm) that are temperature-stabilized for accurate measurements. A Visual Fault Locator is also included for near-end visual fault location and visual fiber identification. Two connector options are available (ST or SC).

Kit Contents

Power Meter:	Micro OWL 2
Light Source:	WaveSource SM/VFL
Accessories:	OWL Reporter software Product manuals Download cable 9-volt batteries NIST certificate Carrying case Protective rubber boots



Features

Fiber optic link certification of singlemode fiber links at 1310nm and 1550nm against a myriad of cabling standards, including two user-customizable standards

Data storage for up to 1000 data points including run labels, fiber type, and link information including link name, date, reference power values, fiber length, and number of splices and interconnects

Built-in loss wizard for calculation of maximum allowable loss values (link budget)

RS-232 interface for continuous data logging, report printing, or data downloading

OWL Reporter software for printing formatted fiber certification reports

Absolute or relative mode for giving you instant pass/fail results

Selectively view, delete or resample data points

Near-end visual fault location

Visual fiber identification

Supported Cabling Standards

EIA/TIA 568
ISO/IEC 11801
10-Gig Ethernet
100Base-SX/LX
100Base-FX
10Base-FB/FL
FDDI
ATM-155/622
Fibre Channel
Token Ring

Also supports 2 user-customizable standards



MADE IN USA

N.I.S.T. Traceable

Product manuals come in PDF format on CD. Adobe Acrobat Reader™ is required to view these documents.

Patch cables are available for an additional charge. Contact OWL for more information.



o.w.l. MANUFACTURER OF QUALITY OPTICAL FIBER TEST EQUIPMENT
OPTICAL WAVELENGTH LABORATORIES™



Optical Wavelength Laboratories (OWL)
N9623 West US Hwy 12
Whitewater, WI 53190
Phone (262)473-0643 Fax: (262)473-8737
<http://owl-inc.com>

Micro OWL 2/WaveSource SM/VFL Test Kit

Singlemode Fiber Test Kit

SKU: KIT-M2-WSVSDst
SKU: KIT-M2-WSVSDsc

Specifications

Micro OWL 2 Optical Power Meter

Detector Type	InGaAs
Calibrated Wavelengths	850, 980, 1300, 1310, 1490, 1550nm
Measurement Range	+5 to -70 dBm
Accuracy	±0.15 dB
Resolution	0.01 dB
Battery Life	up to 100 hours (9V)
Connector Type	2.5/1.25mm Universal
Data Storage Points	up to 1000
Download Data Points	OWL Reporter Software
Power Units Displayed	dBm, dB, µW
Battery Capacity Display	Yes
Backlight	Yes
NIST Traceable	Yes
Auto-shutdown	Yes
Operating Temperature	-10 to 55 C
Storage Temperature	-30 to 70 C
Width	3.48"
Height	6.48"
Depth	1.1"
Weight	373g (12 oz.)

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

WaveSource SM/VFL Singlemode Laser Source

Launch Method	FP Laser
Connector	ST or SC
Center Wavelength (1310 nm)	1310 ±30 nm
Center Wavelength (1550 nm)	1550 ±30 nm
Spectral Width (FWHM; 1310 / 1550 nm)	2 nm
Output Power	-10.0 dBm
Initial Accuracy	0.1 dB
Fiber Type	singlemode
Battery Capacity Display	Yes
Operating Temperature	-20 to +70° C
Storage Temperature	-40 to +85° C
Width	2.75"
Height	4.94"
Depth	1.28"
Weight	154g

Visual Fault Locator Specifications

Launch Method	Laser
Center Wavelength	650 nm
Output Power	-2.0 dBm
Fiber Type	single-mode

Conforms to the Harmonized European Standards EN 61326-1 and EN 61010-1.

